



Елемент	Поз.	Сечение	Дължина [mm]	Бр.	Тегло [kg]	Площ [m2]	Материал	Забележки	Ед. тегло [kg]	Бр.	Общо [kg]	Общо [m2]
C-1	UPN120	2990	1	13.40	40.1	1.30	S 235 JR		41	18	738	23.4
C-2	UPN120	5990	1	13.40	80.3	2.60	S 235 JR		81	139	11259	361.4
C-3	UPN120	2740	1	13.40	36.7	1.19	S 235 JR		37	1	37	1.2
C-4	UPN120	3895	1	13.40	52.2	1.69	S 235 JR		53	1	53	1.7
C-5	UPN120	7610	1	13.40	102.0	3.30	S 235 JR		102	1	102	3.3
C-6	UPN120	7890	1	13.40	105.3	3.41	S 235 JR		106	7	742	23.9
C-7	UPN120	3600	1	13.40	48.2	1.56	S 235 JR		49	1	49	1.6
C-8	UPN120	2250	1	13.40	30.2	0.98	S 235 JR		31	1	31	1.0
C-9	UPN120	2550	1	13.40	34.2	1.11	S 235 JR		35	1	35	1.1
C-10	UPN120	4050	1	13.40	54.3	1.76	S 235 JR		55	1	55	1.8
C-11	UPN120	2850	1	13.40	38.2	1.24	S 235 JR		39	1	39	1.2
C-12	UPN120	6250	1	13.40	83.8	2.71	S 235 JR		84	1	84	2.7
C-13	UPN120	3800	1	13.40	50.9	1.65	S 235 JR		51	1	51	1.6
C-14	UPN120	3350	1	13.40	44.9	1.45	S 235 JR		45	1	45	1.5
C-15	UPN120	2850	1	13.40	38.2	1.24	S 235 JR		39	1	39	1.2
C-16	UPN120	2350	1	13.40	31.5	1.02	S 235 JR		32	1	32	1.0
C-17	UPN120	1900	1	13.40	25.5	0.82	S 235 JR		26	1	26	0.8
C-18	UPN120	1400	1	13.40	18.8	0.61	S 235 JR		19	1	19	0.6
C-19	UPN120	900	1	13.40	12.1	0.39	S 235 JR		13	1	13	0.4
C-20	UPN120	450	1	13.40	6.0	0.20	S 235 JR		7	1	7	0.2
C-21	UPN120	9500	1	13.40	127.3	4.12	S 235 JR		128	7	896	28.9
L100/50/6	L100/50/6	210000	1	6.84	1436.4	61.32	S 235 JR		1437	1	1437	61.3
										total=	15789 kg	
											521.7 m2	

Поз	Сечение	Дължина [mm]	Бр.	Тегло [kg]	Площ [m2]	Материал	Забележки	Ед. тегло [kg]	Бр.	Общо [kg]	Общо [m2]	
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	17	120	2040	64.2
2	8 x 300	370	1	18.84	7.0	0.23	S 235 JR	отв. ф15				
3	8 x 96	200	4	6.03	4.8	0.17	S 235 JR	по-детайл				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	12	113	1356	39.7
4	8 x 220	300	1	13.82	4.1	0.14	S 235 JR	отв. ф15				
5	8 x 90	96	4	5.65	2.2	0.08	S 235 JR	по-детайл				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	15	140	2100	65.4
6	8 x 300	300	1	18.84	5.7	0.19	S 235 JR	отв. ф15				
7	8 x 96	170	4	6.03	4.1	0.15	S 235 JR	по-детайл				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	9	36	684	21.4
8	8 x 300	400	1	18.84	7.5	0.25	S 235 JR	отв. ф15				
9	8 x 96	250	4	6.03	6.0	0.21	S 235 JR	по-детайл				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	25	28	700	22.8
10	8 x 300	550	1	18.84	10.4	0.34	S 235 JR	отв. ф15				
11	8 x 96	400	4	6.03	9.6	0.34	S 235 JR	по-детайл				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	8	13	104	3.2
12	8 x 180	200	1	11.30	2.3	0.08	S 235 JR	отв. ф15				
13	8 x 50	146	2	3.14	0.9	0.04	S 235 JR	по-детайл				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
14	15 x 300	450	1	35.33	15.9	0.29	S 235 JR	отв. ф22	80	10	800	20.3
15	10 x 300	580	2	23.55	27.3	0.73	S 235 JR	отв. ф22				
16	10 x 70	450	2	5.50	4.9	0.15	S 235 JR	по-детайл				
17	10 x 95	450	4	7.46	13.4	0.39	S 235 JR	по-детайл				
18	10 x 280	816	1	21.98	17.9	0.48	S 235 JR	по-детайл/отв. ф33				
HLTI HIT RE 500-V3 c HIT-V(8.8) M20x220 8												
1	10 x 200	300	1	15.70	4.7	0.13	S 235 JR	отв. ф15	9	35	315	9.3
19	8 x 150	300	1	9.42	2.8	0.10	S 235 JR	отв. ф15				
20	8 x 40	96	4	2.51	1.0	0.04	S 235 JR	отв. ф15				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x220 4												
21	[40/4	690	1	4.39	3.0	0.10	S 235 JR	по-детайл	6	22	132	4.6
22	[40/4	350	1	4.39	1.5	0.05	S 235 JR	отв. ф15				
23	8 x 60	160	1	3.77	0.6	0.02	S 235 JR	отв. ф15				
24	8 x 80	160	1	5.02	0.8	0.03	S 235 JR	отв. ф15				
HLTI HIT RE 500-V3 c HIT-V(8.8) M12x110 4												
	[40/4	6060	1	4.39	26.6	0.91	S 235 JR	по-детайл	27	8	216	7.3
	[40/4	4000	1	4.39	17.6	0.60	S 235 JR	по-детайл	18	2	36	1.2
	[40/4	5300	1	4.39	23.3	0.80	S 235 JR	по-детайл	24	2	48	1.6
									total=	8531 kg		
										261.0 m2		